

## MULTI-PURPOSE D3/M ATF

**MOLEC® MULTI-PURPOSE D3/M ATF** is a premium quality Automatic Transmission Fluid that is formulated with premium base stocks and advanced additive technology. Its responsive lowtemperature fluidity is beneficial in both electronic and hydraulic controlled transmissions and transaxles.

**MOLEC® MULTI-PURPOSE D3/M ATF** provides exceptional wear and oxidation control, smooth and consistent shift performance, excellent wear protection and shudder resistance, and resists thickening and high temperature breakdown.

## **TECHNICAL DATA:**

SPECIFICATIONS	ASTM	MULTI-PURPOSE D3/M ATF
Product Number		50211
Viscosity @ 100°C, cSt	D445	7.179
Viscosity @ 40°C, cSt	D445	33.72
Viscosity Index	D2270	184
Specific Gravity @ 60°F	D4052	0.8472
Pour Point, °C	D5950	-48
BROOKFIELD @ -40°C, CP	D2983	14,700
Colour ASTM	VISUAL	RED

## **APPLICATIONS:**

Recommended for use in most domestic and imported automatic transmissions produced prior to 2006 where DEXRON III or MERCON; Ford M2C138-CJ and M2C166-H; ALLISON C-4 and TES389; CATERPILLAR TO-2 fluids are required (1). This fluid can also be used as Power Steering Fluid for most US Manufactured cars (2)

(1) Except for those that require Mercon V ATF, DEXRON VI, CVT, Ford Type F, and under warranty Allison C-4.
Consult your owners manual regarding its suitability as ATF in imported vehicles.

(2) Do not use in Honda power steering fluid systems.

**AVAILABLE PACKAGING:** • 946ML Bottles • 4.73L Jugs

PRODUCT CODES: 50211

## WHEN QUALITY MATTERS®